



**Cycle Gard® Max flow - spring rating**

<b>Model</b>	<b>Max GPM</b>	<b>GPM tank fill rate</b>	<b>Spring Range</b>
1/2" Cycle Gard® I	18	1	15-75/150
3/4" Cycle Gard® I	18	1	15-75/150
1" Cycle Gard® I	25	1	15-75/150
1" Cycle Gard® IV	25	1	15-75/150
1-1/4" Cycle Gard® I	25	1	15-75/150
1-1/4" Cycle Gard® I Hy-Flow	70	1	15-75/150
1-1/2" Cycle Gard® I	70	1	15-75/150
2" Cycle Gard® I	70	1	15-75/150
1" Hydrostat®	25	1	35-65
1-1/2" Cycle Gard® CI	70	Adjustable 1-10	25-175
2" Cycle Gard® CI	110	Adjustable 1-10	25-175
3" Cycle Gard® CI	240	Adjustable 1-10	25-175
4" Cycle Gard® CI	440	Adjustable 1-10	25-175
6" Cycle Gard® CI	1000	Adjustable 1-10	25-175
8" Cycle Gard® CI	1800	Adjustable 1-10	25-175
1-1/4" & 1-1/2" Cycle Gard® II	70	Adjustable 1-10	25-175/30-300
2" Cycle Gard® II	110	Adjustable 1-10	25-175/30-300
2-1/2" Cycle Gard® II	160	Adjustable 1-10	25-175/30-300
3" Cycle Gard® II	240	Adjustable 1-10	25-175/30-300
4" Cycle Gard® II	440	Adjustable 1-10	25-175/30-300
6" Cycle Gard® II	1000	Adjustable 1-10	25-175/30-300
8" Cycle Gard® II	1800	Adjustable 1-10	25-175/30-300
10" Cycle Gard® II	2600	Adjustable 1-10	25-175/30-300
12" Cycle Gard® II	4000	Adjustable 1-10	25-175/30-300

**!!!!Flow rates based on 10ft/sec!!!!**